# REMOVEMYGRAFFITI

SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP Preparation Date: January 5, 2019

### 1. IDENTIFICATION

### Product identifier

**Product Name - BEAVER BITE/GRAFFITI SYRUP** 

### Other means of identification

Product Code(s) SDS570A, SDS911

Recommended use of the chemical and restrictions on use

Recommended Use: Porous Surface Graffiti Remover

Restricted Uses No information available

Emergency telephone number

24 Hour Emergency Phone Number (CANUTEC): 1-888-226-8832 (1-888-CAN-UTEC)

### 2. HAZARD IDENTIFICATION

### Hazardous Classification of the substance or mixture

Flammable liquids - Category 4

Acute toxicity - Oral Category 4

Acute toxicity - Dermal Category 4

Acute toxicity - Inhalation (Dusts/Mists) Category 4

Skin corrosion/irritation Category 2

### Initial Supplier Identifier

Concept Manufacturing Ltd. 1285 Stevens Road West Kelowna BC V1Z 2S9

Tel: 250.491.5656

Distributed By: @removemygraffiti West Kelowna BC V1Z 3X8 1.866.214.7873 1.250.860.8883

### **Label elements**

### Hazard pictograms



### Signal Word: Warning **Hazard statements**

Combustible liquid Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes skin irritation

### **Precautionary Statements**

### Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

#### Response

Specific treatment (see first aid instructions on label)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

### Storage

Store in a well-ventilated place

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity No information available

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No	Weight-%	Synonyms
Benzyl Alcohol	100-51-6	60 - 90%	Benzyl Alcohol
Decyl Glucoside	68515-73-1	5 – 10%	APG

### 4. FIRST AID

### **Description of first aid measures**

## General advice

Show this safety data sheet to the doctor in attendance.

### Inhalation

Remove to fresh air

### Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.

### Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

### Ingestion

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

### Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

### Most important symptoms and effects, both acute and delayed:

Prolonged or repeated contact may cause defatting and drying of the skin. May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause eye damage. Can cause redness, irritation, tearing, pain. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. May cause irritation, redness, pain and tissue injury.

Large doses may cause sore throat, coughing, labored respiration, dizziness, dullness, abdominal pain, vomiting, central nervous system depression, convulsions, and death due to respiratory failure. May be absorbed into the bloodstream with symptoms similar to ingestion.

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

### Indication of any immediate medical attention and special treatment needed:

#### Note to physicians

Treatment based on sound judgment of physician and individual reactions of patient.

### 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

### Specific hazards arising from the substance or mixture

Use water spray to cool fire-exposed containers and structures. Isolate and restrict area access. Do not use a solid stream of water; this may cause spattering and spread the fire.

### **Hazardous combustion products**

Carbon monoxide. Carbon dioxide.

### Special protective equipment for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

### **Environmental precautions**

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

### Methods and materials for containment and cleaning up

Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks and flame. Launder contaminated clothing prior to reuse. Protect from freezing. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers may contain hazardous product residues.

Handle and open containers with care. Protect against physical damage. DO NOT reuse empty containers with out commercial cleaning or reconditioning.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, away from heat and ignition sources. Place away from incompatible materials. Do not reuse containers. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid).

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Limits** This product, as supplied, does not contain any hazardous materials with

occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	Alberta OEL	British Columbia OEL	Ontario	Quebec OEL	Exposure Limit - ACGIH	Immediately Dangerous to Life or Health - IDLH
Benzyl Alcohol 100-51-6	Not available	Not available	Not available	Not available	Not available	Not available

Consult local authorities for recommended exposure limits

### **Appropriate engineering controls**

### **Engineering controls**

Use process enclosure, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Chemical goggles; also wear a face shield if splashing hazard exists.

#### Hand protection

Appropriate chemical resistant gloves should be worn. Impervious gloves.

### Skin and body protection

Boots. Apron, coveralls and/or other resistant protective clothing.

### Respiratory protection

If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator. In case of spill or leak resulting in unknown concentration, use a NIOSH approved supplied air respirator. Warning: Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

### General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance

Physical state Liquid

ColorClear/ ColorlessOdorFaint aromatic

Odor threshold No information available
Explosive properties No information available.
Oxidizing properties No information available.
Molecular weight 108.14

VOC Percentage Volatility
Liquid Density

No information available
No information available

PROPERTIES <u>Values</u> <u>Remarks • Method</u>

**pH** 10

Melting point / freezing point -15 °C / 5 °F

Initial boiling point/boiling range205 °C / 401 °FNone knownFlash point93 °C / 199 °FClosed cup.Evaporation rate1.8 (Ether=1)No data availableNone knownFlammability Limit in AirNone known

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

Upper flammability limit:No data availableLower flammability limit:No data available

Vapor pressure 0.15 mmHg @ 25°C (77°F)

Relative vapor density 3.72

Specific Gravity 1.04 @ 20°C

Water solubility 1g/25 ml water @ 17°C Solubility in other solvents No data available

Partition coefficient No data available None known

Autoignition temperature 436 °C / 817 °F

**Decomposition temperature** No data available None known

Kinematic viscosity 5.8 cP @ 20°C

Dynamic viscosity No data available None known

PROPERTIES Values Remarks • Method

**Explosive properties**No information available. **Oxidizing properties**No information available.

Molecular weight 108.14

VOC Percentage Volatility
Liquid Density

Bulk density

No information available
No information available
No information available

### 10. STABILITY AND REACTIVITY

### Reactivity/Chemical Stability

Stable under ordinary conditions of use and storage. Undergoes slow oxidation in the presence of air or oxygen to form benzaldehyde and benzoic acid.

### Possibility of hazardous reactions

No additional remark.

### Hazardous polymerization

When heated past 100°C, Benzyl Alcohol containing hydrogen bromide and dissolved iron may polymerize with a rapid increase in temperature.

### Conditions to avoid

Incompatible materials. Avoid excessive heat, open flames and all ignition sources. Heat.

### Incompatible materials

Oxidizing agents. Acids. Aluminum. Will attack some plastics.

### Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

### Inhalation

Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. May be absorbed into the bloodstream with symptoms similar to ingestion.

### Eye contact

May cause eye damage. Can cause redness, irritation, tearing, pain.

### Skin contac

Prolonged or repeated contact may cause defatting and drying of the skin. May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause irritation, redness, pain and tissue injury.

### Ingestion

Large doses may cause sore throat, coughing, labored respiration, dizziness, dullness, abdominal pain, vomiting, central nervous system depression, convulsions, and death due to respiratory failure.

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

### Information on toxicological effects

### **Symptoms**

Rats exposed orally to 800 mg/kg benzyl alcohol for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No Observed Adverse Effect Level (NOAEL) was 400 mg/kg.

No evidence of carcinogenicity was seen in a two-year study with rats and mice.

### **Numerical measures of toxicity**

### **Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1,230.00 mg/kg
ATEmix (dermal) 2,000.00 mg/kg
ATEmix 1.50 mg/l
(inhalation-dust/mist)

Unknown acute toxicity No information available

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Benzyl Alcohol 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Skin corrosion/irritation

Prolonged or repeated contact may cause defatting and drying of the skin. May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause irritation, redness, pain and tissue injury.

### Serious eye damage/eye irritation

May cause eye damage. Can cause redness, irritation, tearing, pain.

### Respiratory or skin sensitization

No information available.

### Germ cell mutagenicity

No information available.

### Carcinogenicity

No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Benzyl Alcohol 100-51-6	Not available	Not available	Not available	Not available

### Reproductive toxicity

No information available.

Specific target organ systemic toxicity - single exposure

No information available.

Specific target organ systemic toxicity - repeated exposure

No information available.

### **Aspiration hazard**

No information available.

# **REMOVEMYGRAFFITI**

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Chemical Name	Ecotoxicity – Freshwater Algae Data	Ecotoxicity - Fish Species Data	Toxicity to microorganisms	Crustacea
Benzyl Alcohol 100-51-6	Not available	10 mg/L LC50 (Lepomis macrochirus) 96 h static460 mg/L LC50 (Pimephales promelas) 96 h static	Not available	EC50: =23mg/L (48h, water flea)

Persistence and degradability No information available.

Bioaccumulation No information available.

### **Component Information**

Chemical Name	Partition coefficient
Benzyl Alcohol 100-51-6	1.1

Other adverse effects No information available.

### 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation. Do not reuse empty containers.

### 14. TRANSPORT INFORMATION

## TDG (Canada):

UN Number Not applicable
Shipping name Not regulated
Class Not applicable
Packing Group Not applicable
Marine pollutant Not available.

### DOT (U.S.)

UN Number Not applicable Shipping name Not regulated Class Not applicable Packing Group Not applicable Marine pollutant Not available

# REMOVEMYGRAFFITI

### SDS570A BEAVER BITE/ SDS911 GRAFFITI SYRUP

### 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

### **U.S. Regulatory Rules**

Chemical Name	CERCLA/SARA - Section 302:	SARA (311, 312) Hazard Class:	CERCLA/SARA - Section 313:
Benzyl Alcohol- 100-51-6	Not Listed	Not Listed	Not Listed

### **International Inventories**

**TSCA** Complies **DSL/NDSL** Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA: **Health hazards** 3 Flammability 2 Instability 0 Physical and chemical properties -Physical hazards 0

**HMIS Health Rating: Health hazards** 3 Flammability 2

Personal protection X

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Prepared By: SDS Division of Concept Manufacturing Ltd.

Preparation Date: January 5, 2019

#### Disclaimer

### NOTICE TO READER:

Concept Manufacturing Ltd. and Remove My Graffiti Inc. expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a Product Specification Sheet and/or a Certificate of Analysis.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized

technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.