

**SECTION 1: Identification**
**1.1. Product identifier**

Product form : Mixture  
 Product name : INTERIOR FLAT ACRYLIC LATEX CEILING WHITE  
 Product code : 03360  
 Product group : Trade product

**1.2. Recommended use and restrictions on use**

Recommended use : Coatings and paints

**1.3. Supplier**

Cloverdale Paint Inc.  
 400- 2630 Croydon Drive  
 V3Z 6T3 SURREY - CANADA  
 T 1-(604)-596-6261  
[www.cloverdalepaint.com](http://www.cloverdalepaint.com)

**1.4. Emergency telephone number**

Emergency number : 613-996-6666

**SECTION 2: Hazard identification**
**2.1. Classification of the substance or mixture**
**Classification (GHS-CA)**

Skin sensitisation, Category 1      H317  
 Carcinogenicity, Category 1      H350  
 Specific target organ toxicity — Repeated exposure, Category 1      H372  
 Hazardous to the aquatic environment — Acute Hazard, Category 3      H402  
 Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements**
**GHS-CA labelling**

Hazard pictograms (GHS-CA) :

  
 GHS07

  
 GHS08

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H317 - May cause an allergic skin reaction.  
 H350 - May cause cancer.  
 H372 - Causes damage to organs through prolonged or repeated exposure.  
 H402 - Harmful to aquatic life

Precautionary statements (GHS-CA) : P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P260 - Do not breathe mist, vapours, spray.  
 P264 - Wash Skin thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.  
 P273 - Avoid release to the environment.  
 P280 - Wear eye protection, face protection, protective gloves, protective clothing.  
 P302+P352 - IF ON SKIN: Wash with plenty of soap & water.  
 P314 - Get medical advice/attention if you feel unwell.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

**2.3. Other hazards**

Other hazards not contributing to the classification : None under normal conditions.

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 2.4. Unknown acute toxicity (GHS-CA)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
Titanium Dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO <sub>2</sub> ) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide	(CAS-No.) 13463-67-7	7.7	Carc. 2, H351
Latex Resin			6.9	Skin Sens. 1, H317
Limestone	Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl	(CAS-No.) 1317-65-3	4.8	Carc. 1A, H350 STOT RE 1, H372

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.
Potential adverse human health effects and symptoms	: Harmful if swallowed. Irritation: may cause irritation to the respiratory system.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Unsuitable extinguishing media

No additional information available

### 5.3. Specific hazards arising from the hazardous product

Fire hazard	: Not flammable.
-------------	------------------

### 5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Absorb spillage to prevent material damage.
------------------	---

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 6.2. Methods and materials for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe mist, vapours, spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from freezing. Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Titanium Dioxide (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
New Foundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf
Limestone (1317-65-3)		
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (total)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Limestone (1317-65-3)		
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white
Odour	: ammonia-like
Odour threshold	: No data available
pH	: 8.5 - 9.5
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flash point	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable Not applicable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Specific gravity	: 1.563
Density	: 13.03 lb/gal
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : < 45 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Oxidizing agent. Strong acids. Strong bases.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
Skin corrosion/irritation	: Not classified pH: 8.5 - 9.5
Serious eye damage/irritation	: Not classified pH: 8.5 - 9.5
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Harmful if swallowed. Irritation: may cause irritation to the respiratory system.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
-------------------	----------------------------

#### 12.2. Persistence and degradability

<b>INTERIOR FLAT ACRYLIC LATEX CEILING WHITE</b>	
Persistence and degradability	Not established.

#### 12.3. Bioaccumulative potential

<b>INTERIOR FLAT ACRYLIC LATEX CEILING WHITE</b>	
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

<b>INTERIOR FLAT ACRYLIC LATEX CEILING WHITE</b>	
Mobility in soil	Not Established

#### 12.5. Other adverse effects

Other information	: Avoid release to the environment.
-------------------	-------------------------------------

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

UN-No. (TDG) : Not Regulated  
Transport document description : Not Regulated

### 14.2. Transport information/DOT

#### Department of Transport

DOT NA no. : Not Regulated

Transport document description : Not Regulated Consumer commodity  
Proper Shipping Name (DOT) : Consumer commodity  
Contains Statement Field Selection (DOT) :

Dangerous for the environment : No

DOT Packaging Exceptions (49 CFR 173.xxx) : 167  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 167  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 30 kg gross  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 kg gross

Emergency Response Guide (ERG) Number : 171

Other information : No supplementary information available.

### 14.3. Air and sea transport

#### IMDG

UN-No. (IMDG) : Not Regulated  
Transport document description (IMDG) : UN Not Regulated

#### IATA

UN-No. (IATA) : Not Regulated  
Transport document description (IATA) : UN Not Regulated

## SECTION 15: Regulatory information

### 15.1. National regulations

#### INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

Listed on the Canadian DSL (Domestic Substances List)

#### Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

### 15.2. International regulations

#### Titanium Dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# INTERIOR FLAT ACRYLIC LATEX CEILING WHITE

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### Limestone (1317-65-3)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Latex Resin

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

## SECTION 16: Other information

Date of issue : 04/04/2017

Revision date : 11/15/2019

Other information : None.

Full text of H-statements:

H317	May cause an allergic skin reaction.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life

SDS Canada (GHS) - Cloverdale

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*